

SLIDING SHOWER ENCLOSURE

ZT / SERIE 7000





© Copyright 2024 Vismaravetro srl

Sliding shower enclosure for rounded shower trays (R=55 cm) The fixed glass parts are inserted into profiles with self-locking seals, guaranteeing an absolute overall stability and excellent water resistance, without use of silicone for bonding and sealing components. The perfect sliding of the doors is guaranteed by rollers with ball bearings. It also suitable for asymmetric shower trays. R=55 cm

Serie 7000 is a collection of shower enclosures with sliding shower doors which embodies the essence of our experience developed over years of designing and making shower enclosures. The doors slide thanks to a ball bearing slider system, fixed to the glass and supported by a reduced size profile, yet still big enough to support the door without bending or sinking from the weight of the door itself. Serie 7000 is a complete system that can be adapted to a wide range of measurements and used for recessed, corner or wall solutions.

Design Centro Progetti Vismara

DIMENSIONS

L: Min 78 - Max 101 cm H standard: 195 cm



PLUS BALL BEARINGS, FIXED DIRECTLY TO THE STOPPERS VERTICAL ADJUSTMENT OF THE DOOR GLASS, WITH FLAT SCREWS. PRODUCT WITH CE MARKING THIS MODEL IS PRODUCED WITHOUT SILICON TPA TREATMENT PREVENTING LIMESCALE Vismaravetro uses a innovative technology Product conforming to EN14428:2015 with CE "TPA" for protecting the glass surfaces of marking shower enclosures. The glass surface is treated with a polymer which limits the adhesive properties of residues such as limescale, grease and soap deposits. The $\ensuremath{\mathsf{TPA}}$ treatment helps with the cleaning and removal of the lime scale deposits and residues from the glass. AVAILABLE WITH BLACK RUBBER SEALS (PROFILES 09 AND 39) Products realized with Matt Black (09) or Metal Gun (39) finishes are equipped with black rubber seals



COMPONENTS



ZT

SHOWER ENCLOSURES WITH SLIDING DOORS FOR ROUND TRAYS (R. 55 CM)

CHARACTERISTICS

- Extensible 3 cm each side.
- Magnetic strips
- Vertical adjustment of doors
- Ball bearings
- Stoppers
- Product with CE marking
- Horizontal and vertical adjustment, after installation accomplished

MATERIALS

- Tempered safety glass 6 mm.
- Anodised or enamelled aluminium profile.

DIMENSIONS

L: Min 78 - Max 101 cm H: Min 195 - Max 195 cm H standard: 195 cm



COMPLEMENT ELEMENTS



KNOBS AND HANDLES M8Z STANDARD

PROFILES



ANODISED PROFILES 21 -BRIGHT SILVER



ANODISED PROFILES 31 -SATIN SILVER



ANODISED PROFILES 84 -BOND COPPER



ANODISED PROFILES 09 -MATT BLACK



ANODISED PROFILES 38 - MOKA



VARNISHED PROFILES 14 -WHITE



VARNISHED PROFILES 13 -LIGHT BLU



VARNISHED PROFILES 15 -MATT WHITE



VARNISHED PROFILES 07 -YELLOW



VARNISHED PROFILES 11 -GREY



VARNISHED PROFILES 10 -PERGAMON



VARNISHED PROFILES 05 -RED



VARNISHED PROFILES 12 -GREEN



GLASSES









GLASS PANE 08 - SATIN GLASS

DECORS



OPTIONALS







EQUIPPED COLUMN AMICO



PARTITION PANEL SCREEN



REEN SHOWER TRAY VI.P



TREATMENT LIME SCALE TREATMENT PREVENTING LIMESCALE (TPA)

WHERE TO BUY